NEW!

MACROMATIC

Better. By Design.

Slim Three-Phase Monitor Relays

17.5 mm Enclosure



PBDU SERIES RELAYS

- Three-Phase Monitoring
- Phase Loss
- Phase Reversal
- Adjustable Phase Unbalance
- Universal Voltage: 208 - 480 AC
- 5 Amp SPDT Contact

New PBDU Series Phase Monitors protect motors and equipment from damage due to voltage faults on three-phase systems.

The compact 17.5 mm enclosure for DIN-rail mounting conserves space and reduces installation time.

The PBDU Series continuously monitors all voltages with LED status indication.

c UL us CE

SPECIFICATIONS

Input:	208V AC – 480V AC +/- 10%
	Tripping Delay, 100 ms Fixed
	Unbalance adjustment, 5-25% or OFF
	Supply voltage = Measured voltage
	Reset time, 500 ms
	Drop out voltage = >20% of supply voltage
Output:	1 – SPDT 250V AC, 5 Amp
	Mechanical Life, 20,000,000 Operations
	Electrical Life, 200,000 Operations
Indication:	Green - Power ON
	Amber - Fault

www.macromatic.com **800.238.7474**

Macromatic Industrial Controls, Inc. • 2201 Corporate Drive • Waukesha, Wisconsin 53189
800.238.7474 • 262.781.3366 • sales@macromatic.com • www.macromatic.com

07/18/2022