



TRYSTAR®

Termination Box, Lug to Lug



TBLTL Series



Termination Box, Lug to Lug

TERMINATION BOX LUG TO LUG

LUG TO LUG TERMINATION CABINET SERVES TO PROVIDE PERMANENT CONNECTION VIA LUGS ON INCOMING AND OUTGOING TERMINATIONS

CABINET IS WALL MOUNTED AND IS AVAILABLE IN TYPE 3R PAINTED ENCLOSURE OR TYPE 3R 316 STAINLESS STEEL

AVAILABLE WITH PILOT LIGHT INDICATORS FOR VOLTAGE PRESENT FOR ALL THREE PHASES

AVAILABLE WITH OR WITHOUT CAM LOKS FOR LOAD BANK TESTING

AVAILABLE WITH FLUKE IR VIEWING WINDOWS FOR THERMAL SURVEYS

UL 1773 Listed USL Termination Box

200-5000 Amp



Features

Features

TYPE 3R ENCLOSURE ANSI 61 GRAY

TYPE 3RSS 316 STAINLESS STEEL ENCLOSURE

OPTIONAL PILOT LIGHT INDICATION FOR VOLTAGE PRESENT

RATED THROUGH 600VAC 3 OR 4 WIRE

BUS BAR SIZED 1000A/SQ INCH, FULLY RATED

100% TESTED AT FULL VOLTAGE

PHASE REVERSAL PROTECTION RELAY INCLUDED

3 WIRE AUTO START TERMINALS INCLUDED

BOTTOM CAM-LOCK CABLE DOOR IS MECHANICALLY INTERLOCKED AND CAN NOT BE OPENED UNTIL FRONT DOOR IS UNLOCKED AND OPENED

CAM-LOCK RECEPTACLES ARE MOUNTED AT AN ANGLE TO HELP WITH CONNECTING THE CABLE TO THE RECEPTACLE



TRYSTAR®